



NM34 is a brass NMO 3/4" mount for mobile antennas.

NM34 is well suited for heavy duty use because of its stainless steel and brass construction and PTFE insulator, in all kind of weather.

It has SH O-rings to avoid water migration.

FEATURES

- Gold Plated Brass Lock Nut
- Long Life: 10+ years
- Brass connector
- NMO 3/4" mount
- 50 ohms impedance
- VSWR: 1.5:1

Electrical Specifications

Frequency Range	DC - 1 Ghz
VSWR	< 1.5:1
Impedance	50 ohms
Maximum Power	200 watts
Body	Straight
Operational Temperature	-40°C to +80°C
Attachment	Crimp /Solder
Insulator	PTFE
Contact	Brass
O-rings	SH
Cap	Plastic
Weigth	30 g

Models and Kits

NM34	NMO 3/4" mount only, without cable and connector
NM34-58U	NMO 3/4" mount with 5 meters of RG-58/U cable
NM34-58U-MU	NMO 3/4" mount with 5 meters of RG-58/U cable and Mini UHF Male Crimp Connector
NM34-58U-PL	NMO 3/4" mount with 5 meters of RG-58/U cable and PL-259 Male Crimp Connector
NM34-58U-T	NMO 3/4" mount with 5 meters of RG-58/U cable and TNC Male Crimp Connector