

NMO 3/4" Trunk Lid Mount, NM34-TL



FEATURES

- Stainless Steel Construction
- Plated Brass Lock Nut
- Long Life: 10+ years
- Gold Plated connector
- NMO 3/4" mount
- 50 ohms impedance
- VSWR: 1.5:1

NM34-TL is a NMO 3/4" trunk lid mount for mobile antennas.

NM34-TL is well suited for heavy duty use because of its stainless steel, gold plated brass construction and PTFE insulator.

It has SH O-rings to avoid water migration and two oppression screws.

Electrical Specifications

| | |
|-------------------------|----------------|
| Frequency Range | DC - 1 Ghz |
| VSWR | < 1.5:1 |
| Impedance | 50 ohms |
| Maximum Power | 200 watts |
| Operational Temperature | -40°C to +80°C |
| Attachment | Crimp |
| Insulator | PTFE |
| Contact | Gold Plated |
| O-rings | SH |
| Cap | Plastic |

Models and Kits

| | |
|----------------|---|
| NM34-TL | NMO 3/4" trunk lid mount only, without cable and connector |
| NM34-TL-58U | NMO 3/4" trunk lid mount with 5 meters of RG-58/U cable |
| NM34-TL-58U-MU | NMO 3/4" trunk lid mount with 5 meters of RG-58/U cable and Mini UHF Male Crimp Connector |
| NM34-TL-58U-PL | NMO 3/4" trunk lid mount with 5 meters of RG-58/U cable and PL-259 Male Crimp Connector |
| NM34-TL-58U-T | NMO 3/4" trunk lid mount with 5 meters of RG-58/U cable and TNC Male Crimp Connector |