

NMO 3/4" L Type Mount, NM34-LL



FEATURES

- Plated Brass Lock Nut
- Long Life: 10+ years
- Brass connector
- NMO 3/4" mount
- 50 ohms impedance
- VSWR: 1.5:1

NM34-LL is a NMO 3/4" "L" type bracket mount for mobile antennas.

NM34-LL is well suited for heavy duty use because of its stainless steel construction.

It can be ordered as a kit with mount, cable and connector or only bracket.

Electrical Specifications (Mount)

Frequency Range	DC - 1 Ghz
VSWR	< 1.5:1
Impedance	50 ohms
Maximum Power	200 watts
Operational Temperature	-40°C to +80°C
Attachment	Crimp /Solder
Insulator	PTFE
Contact	Brass
O-rings	SH
Cap	Plastic

Models and Kits

NM34-LL	"L" type bracket only, without cable and connector
NM34-LL-58U	"L" type bracket with NMO 3/4" mount and 5 meters of RG-58/U cable
NM34-LL-58U-MU	"L" type bracket with NMO 3/4" mount, 5 meters of RG-58/U cable and Mini UHF Male Connector
NM34-LL-58U-PL	"L" type bracket with NMO 3/4" mount, 5 meters of RG-58/U cable and UHF (PL-259) Crimp Connector
NM34-LL-58U-B	"L" type bracket with NMO 3/4" mount, 5 meters of RG-58/U cable and BNC Male Connector